

Publication number: JP11164887 (A)

Publication number: JP11164887 (A)

Publication date: 1999-06-22

Inventor(s): MINAMI KOJI; OBARA TEIJI +

Applicant(s): NIPPON ZEON CO +

Classification:

- international: A61J1/05; A61M5/178; A61J1/05; A61M5/178; (IPC1-7): A61J1/05; A61M5/178


- **European:**

Application number: JP19970352411 19971205

Priority number(s): JP19970352411 19971205

Abstract of JP 11164887 (A)

PROBLEM TO BE SOLVED: To provide a cylindrical molding having a small resistance in separation from a die in injection molding, hardly generating residual stress, and improved in mechanical strength, solvent crack resistance and steam sterilization resistance. **SOLUTION:** This invention relates to a cylindrical molding 2 integrally formed of a cyclic hydrocarbon resin having a monocyclic (especially preferable is a six-membered ring) alicyclic structure in the main chain or a branch chain, the draft taper angle of a cylinder main body 4 of the cylindrical molding 2 being 1/1000000 to 1/100, preferably 1/50000 to 1/500, especially preferably in the range of 1/30000 to 1/1000. The intersection part of faces of the cylindrical molding 2 has a curvature. A connection part having a lure lock structure 10 is integrally formed with the cylindrical molding 2. The cylindrical molding is used suitably as a cylinder for syringe for medical care or other use.



Data supplied from the **espacenet** database — Worldwide